

92-675

Disposable Nitrile Glove with Textured Fingertips

Disposable gloves with chemical splash protection, for food processing and heavy-duty handling

- Reliable chemical splash protection: TouchNTuff[®] 92-675 disposable gloves offer protection against accidental exposure when handling a range of chemicals
- Improved durability: A strong, proprietary nitrile formulation gives gloves extra resilience for more durable protection in food handling, lab work or heavy-duty jobs
- Elevated comfort: The soft nitrile formulation enhances comfort during long work days
- Food handling compliance: These gloves are suitable for a wide range of food processing applications
- Enhanced grip: Textured fingertips allow wearers to securely handle objects and equipment



Industries

- Life Sciences
- Chemical
- Food Processing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Handling incoming goods
- Maintenance
- All food processing, applications that have food contact



TECHNICAL DATA SHEET

	Product Information		
External Glove Surface	Textured Fingers		
Audit Standards	ISO 9001		
Product Certification	Category III, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 9001, MT11: CLASSE B		
Packaging Overview	S-XXL: 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case		
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.		
Country Of Origin	Thailand		
Product Segmentation	Robust		
Antistatic	Yes		
Silicone Free	Yes		

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	240 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	4.0 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.11/	4.3	ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.14/ 5.5		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥14	≥14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6	≥6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	565716	565717	565718	565719	92675110

Performance Standards and Regulatory Compliance









For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell, $^{\textcircled{8}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{9}}$ 2025 Ansell Limited. All Rights Reserved.

