

## 55-301 Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

# Neoprene RABS/isolator gloves, designed for medium-duty environments with aggressive chemicals

Port size: 178mm/7"
Thickness: 0.51mm/20 mil

- Specialized protection: AlphaTec® Neoprene Isolator Gloves 55-301 meet EN ISO 374:2016 chemical resistance standards, shielding wearers from most acids, alcohols, oils and lubricants
- Assured dexterity: Medium-level thickness grants these isolator gloves better dexterity, for enhanced usability over a sustained period
- Reduced contamination risks: Their unlined design lessens the chance of chemical absorption and related contamination risks
- Enhanced durability: These neoprene gloves also ensure EN388:2016+A1:2018 Level 2 abrasion resistance

#### **KEY FEATURES & BENEFITS**

- EN ISO 374:2016-compliant chemical resistance: Dependable hand protection
- Medium thickness: Greater dexterity, for simpler parts handling
- Unlined: Minimized contamination risks, easier cleaning







### 55-301

Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

#### **TECHNICAL DATA SHEET**

Product Reference	55-301
Material	Neoprene Polymer
Color	Black
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	9,10
Temperature Range	From -30°C to 50°C
Cleanroom Class	Non-Critical Environment
Shelf Life	Five (5) years from date of manufacture.
Tested For Use With Chemotherapy Drugs	No
Antistatic	No
Standards	CE 0493, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, EN 388:2016, Category III, UKCA





## **55-301**Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	711 / 28	EN 455-2
Port Size	178mm/7"	
Target Single Wall Palm Thickness (mm/mil)	0.51 / 20	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.51 / 20	EN 455-2

#### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 2	
Blade Cut Resistance	Level 1	
Tear Resistance	Level O	
Puncture Resistance	Level O	
ISO 13997 Cut Resistance	Level A	

#### **ORDERING INFORMATION**

	PORT SIZE	7	7
	SIZE	9	10
55-301	REORDER NO.	55301090	55301100

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### **Asia Pacific Region**

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Performance Standards and Regulatory Compliance











Ansell,  $^{\circledR}$  and  $^{\intercal}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\circledR}$  2025 Ansell Limited. All Rights Reserved.

