

94-242 Static Dissipative

Disposable static dissipative gloves

Gloves that reduce risk of fire, explosion, or damage caused by electrostatic discharge

- Ansell's first disposable static dissipative gloves: MICROFLEX® 94-242 gloves reduce the risk of electrostatic discharge, which can cause spontaneous combustion in atmospheric explosive environments
- Low vertical resistivity: Proprietary nitrile formulation infused with an engineered material that channels electricity through the glove polymer, for a low vertical resistance below $10^8~\Omega$
- Advanced protection: Made with TNT™
 Chemical Splash Resistance Technology for soft, durable protection against a wide range of chemicals
- Touchscreen compatibility: Provides capacitive and resistive touchscreen capability when working with industrial electronics
- Improved visibility: Black color provides contrast against potentially combustible dust, while hiding the appearance of oils, dirt and stains



Industries

- Aerospace
- Chemical
- Electronics
- Food Processing
- Life Sciences
- Manufacturing
- Raw material preparation
- Utilities

Recommended For

- Handling chemicals and cleaning materials
- Handling of tools
- Equipment, maintenance and repair
- Food processing and handling
- Unpacking of bulk goods
- Product shipping, transport and delivery
- Packaging and labeling
- Oil, fluids and filter change
- Inspection of parts, equipment



TECHNICAL DATA SHEET

	Product Information		
External Glove Surface	Textured Fingers		
Audit Standards	ISO 13485, ISO 14001, ISO 9001		
Product Certification	Personal Protective Equipment Regulation (EU) 2016/425, Arrette du 05/08/2020, EU Food Contact Approved, EC 2023/2006, ASTM D6319, Dermatest, EN 16350:2014, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, UKCA, CE		
Packaging Overview	Case/Carton=1000 gloves/10 Dispensers; Dispenser=100 gloves		
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.		
Country Of Origin	Thailand		
Product Segmentation	Robust		
Antistatic	Yes EN1149 + EN16350		
Silicone Free	Yes		
Vulcanization Chemical Accelerators	 Zinc Dibutyldithiocarbamate (ZDBC) Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions. 		

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	245 /	9.6	EN ISO 21420
Freedom from Holes (Inspection level I)	1.5 AQL		EN 374-2
Palm Thickness (mm/mils)	0.12/ 4.7		
Finger Thickness (mm/mils)	0.16/ 6.2		
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥14	≥14	ASTM D412 & D573
Elongation at Break (%)	≥500	≥400	ASTM D412
Force at break (N)	≥6	≥6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	94242070	94242080	94242090	94242100	94242110

Performance Standards and Regulatory Compliance















For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5548 8151 info medical in@ansell.com North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050

latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Technology





Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

