

85-502
Non-clean/Non-sterile EPDM
RABS/Isolator Gloves

EPDM RABS/isolator gloves, made with premium FDA-approved material, for fewer glove changes

Port size: 254mm/10" Thickness: 0.4mm/16 mil

- Optimized durability: The AlphaTec® EPDM Isolator Glove 85-502 is designed for repeated autoclave sterilization (up to 50 times), which means fewer replacements
- Assured protection: These RABS gloves are EN ISO 374-compliant, resisting hydrogen peroxide and common disinfecting chemicals
- Increased eco-friendliness: They are halogen-free, making them suitable for disposal by incineration
- Food handling compliance: They comply with FDA Food Contact regulation (FDA Positive List) 21 CFR 177 for Indirect Food Additives

KEY FEATURES & BENEFITS

- **EPDM material:** Ideal for repeated autoclave sterilization
- Chemical resistance: Hydrogen peroxide/common disinfecting chemicals
- FDA food handling compliance: For safe, assured food handling







85-502Non-clean/Non-sterile EPDM RABS/Isolator Gloves

TECHNICAL DATA SHEET

Product Reference	85-502
Material	Ethylene propylene diene rubber_EPDM
Color	Black
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 130°C
Cleanroom Class	Non-Critical Environment
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, EN ISO 374-5:2016, Category III, UKCA





85-502 Non-clean/Non-sterile EPDM **RABS/Isolator Gloves**

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	800/32	EN ISO 21420
Port Size	254mm/10"	
Target Single Wall Palm Thickness (mm/mil)	0.40 / 16	EN 455-2
Target Single Wall Finger Thickness (mm/mil)	0.40 / 16	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.40 /16	EN 455-2

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 2	
Blade Cut Resistance	Level 1	
Tear Resistance	Level 1	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

ORDERING INFORMATION

	PORT SIZE	10"/254mm	10"/254mm
	SIZE	9.5	11
85-502	REORDER NO.	85502095	85502110

Performance Standards and Regulatory Compliance

C € 0493







For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890





Ansell, $^{\circledR}$ and $^{\intercal}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\circledR}$ 2025 Ansell Limited. All Rights Reserved.



