

55-305 Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

Neoprene RABS/isolator gloves, designed to guard against aggressive chemicals in mediumduty environments

Port size: 254mm/10" Thickness: 0.51mm/20mil

- Specialized protection: AlphaTec® Neoprene Isolator Gloves 55-305 meet EN ISO 374:2016 chemical resistance standards, offering wearer protection against most acids, alcohols, oils, and lubricants
- Reduced contamination risks: The unlined nature of AlphaTec® Neoprene Isolator Gloves 55-305 lowers the chance of chemical absorption and related contamination risks
- Enhanced durability: AlphaTec® Neoprene Isolator Gloves 55-305 also satisfy EN388:2016 norms for abrasion resistance, granting them greater durability

KEY FEATURES & BENEFITS

- EN ISO 374:2016-compliant chemical resistance: For reliable protective gloves
- Medium thickness: Improved dexterity, for easier handling
- Unlined: Fewer contamination risks and more efficient cleaning







55-305

Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

TECHNICAL DATA SHEET

| Product Reference | 55-305 |
|---|---|
| Material | Neoprene Polymer |
| Color | Black |
| Shape | Ambidextrous |
| External Glove Surface | Smooth |
| Cuff Style | Beaded |
| Storage Instructions | Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use. |
| Available Sizes | 10 |
| Temperature Range | From -30°C to 50°C |
| Cleanroom Class | Non-Critical Environment |
| Shelf Life | Five (5) years from date of manufacture. |
| Tested For Use With Chemotherapy Drugs | No |
| Antistatic | No |
| Standards | CE 0493, EN 388:2016, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, Category III, UKCA |





55-305Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

PHYSICAL PROPERTIES

| | Typical Values | Testing Method |
|---|----------------|----------------|
| Typical Length (mm/in) | 813 / 32 | EN 455-2 |
| Port Size | 254mm/10" | |
| | | |
| | | |
| Target Single Wall Palm Thickness (mm/mil) | 0.51 / 20 | EN 455-2 |
| Target Single Wall Cuff Thickness (mm/mil) | 0.51 / 20 | EN 455-2 |

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

| Risk | Performance level |
|--------------------------|-------------------|
| Abrasion Resistance | Level 2 |
| Blade Cut Resistance | Level 1 |
| Tear Resistance | Level O |
| Puncture Resistance | Level O |
| ISO 13997 Cut Resistance | Level A |

ORDERING INFORMATION

| | PORT SIZE | 10"/254mm |
|--------|-------------|-----------|
| | SIZE | 10 |
| 55-305 | REORDER NO. | 55305100 |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Performance Standards and Regulatory Compliance

C € 0493









Ansell, $^{\textcircled{8}}$ and $^{\textcircled{m}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{c}}$ 2025 Ansell Limited. All Rights Reserved.

