

# 55-104 Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

## NRL RABS/Isolator gloves, offering tear- and abrasion-resistant hand protection

Port size: 203mm/8"
Thickness: 0.51mm/20 mil

- Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-104 meet EN388:2016 standards, delivering proven Level 2 tear and abrasion resistance
- Improved dexterity: Medium-level thickness ensures these RABS gloves offer dexterous personal protection, for easier handling
- Limited contamination risks: Cleaning these latex gloves is simple, thanks to their translucent, unlined design, less prone to contamination

#### **KEY FEATURES & BENEFITS**

- Latex construction: Heightened defenses against abrasion and tears
- Medium thickness: Enhanced dexterity, for easier parts handling
- Unlined: Reduced contamination risks and an easier cleaning process







### 55-104

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

### **TECHNICAL DATA SHEET**

Product Reference	55-104
Material	Natural Rubber Latex
Color	Natural
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	10
Temperature Range	From -30°C to 50°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, Category III, UKCA
Vulcanization Chemical Accelerators	<ul> <li>Natural rubber proteins</li> <li>Zinc Diethyldithiocarbamate (ZDEC)</li> </ul>





# 55-104 Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	813 / 32	EN 455-2
Port Size	203mm/8"	
Target Single Wall Palm Thickness (mm/mil)	0.51 / 20	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.51 / 20	EN 455-2

### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level
Abrasion Resistance	Level 2
Blade Cut Resistance	Level O
Tear Resistance	Level 2
Puncture Resistance	Level O
ISO 13997 Cut Resistance	Level X

#### **ORDERING INFORMATION**

	PORT SIZE	8"/203mm
	SIZE	10
55-104	REORDER NO.	55104100

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Performance Standards and Regulatory Compliance

**C** € 0493









Ansell,  $^{\circledR}$  and  $^{\intercal}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\circledR}$  2025 Ansell Limited. All Rights Reserved.

