

HyFlex® 11-757 Our lightest ANSI/ISEA 105-2024 CUT A7 and EN ISO F cut resistant glove for

touchscreen compatibility



Durable lightweight industrial gloves, combining advanced cut resistance with superb comfort

- Advanced protection: HyFlex[®] 11-757 light-duty industrial gloves feature INTERCEPT[™] Cut Resistance Technology, providing wearers with superior cut resistance at ANSI/ISEA 105-2024 CUT A7 and EN ISO F* levels
- Enhanced usability: Their ultra-light, ultra-thin design ensures ample dexterity, breathable comfort and touchscreen compatibility, for uninterrupted daily use and optimized productivity
- Improved durability: These HyFlex[®] gloves' palmdipped polyurethane coating also delivers excellent abrasion resistance
- Considered ergonomics: With a tailored fit at the base of the pinky finger, these safety gloves are shaped around natural hand contours
- Assured skin-friendliness: They have also been dermatologically approved by $\text{Dermatest}^{\textcircled{R}}$
- Increased protection: HyFlex 11-757's palm-dipped coating improves durability, while a reinforced thumb crotch defends against rapid wear
 *7x greater than standard ANSI/ISEA 105-2024 CUT A2 and EN ISO B gloves

Industries

- Aerospace
- Automotive
- Machinery and Equipment
- Electronics
- Glass manufacturing
- White Goods

Applications

- Assembly & inspection of components
- Picking, fastening components
- Final assembly
- Applying finish to materials, products
- Applications requiring dexterity and precision
- Handling metal sheets & panels
- Handling of glass sheets, sharpedged objects







HyFlex® 11-757

Our lightest ANSI/ISEA 105-2024 CUT A7 and EN ISO F cut resistant glove for touchscreen compatibility

Key Features

- INTERCEPT™ Cut Resistance Technology: Superior cut resistance*
- Ultra-thin lightweight design: Dexterity and touchscreen compatibility
- Polyurethane (PU) coating: Excellent abrasion resistance
- Thumb crotch reinforcement: Ideal for dry and slightly oily applications

*7x greater than standard ANSI/ISEA 105-2024 CUT A2 and EN ISO B gloves

Performance Standards & Regulatory Compliance

Technologies





Touchscreen Compatible

ANSI/ISEA 105-2024 EN388: 2016 A7 ecovadis /3 AUG 2024

3X31F

<u>d</u>

Specifications

BRAND STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex [®] 11-757	Finishing: Palm dipped, Thumbcrotch reinforcement Coating Material: Polyurethane Liner Material: Nylon, Stainless steel, Polyester, Tungsten Cuff Style: Knitwrist		6, 7, 8, 9, 10, 11	222-274 mm / 8.74 - 10.8 inch	Black	12 pairs/bag, 12 bags/carton

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Europe, Middle East & Arric Ansell Healthcare Europe NV Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Latin America & Caribbean Region Laun America & Cariobeán Kégion Anseil Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C, Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

North America Region Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 900 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Canada Canada 105 Lauder Cowansville, QC J2K 2K8 Canada T: +1 800 363 8340 F: +1 800 267 3551

Australia Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 T: +603 8310 6688 F: +603 8310 6699

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

