

### 11-931

Lightest weight gloves with cut + oil protection for enhanced safety









# Ultralight, palm-coated cut-resistant and oilrepellent work gloves

- Specialized protection: EN ISO B/ANSI A2 cut protection guaranteed, with RIPEL™ Liquid Repellence Technology to prevent oil and liquid contact with the skin
- Targeted defenses: The HyFlex<sup>®</sup> 11-931's reinforced thumb crotch delivers 12x more thumb area resilience
- Improved durability: FORTIX<sup>™</sup> Abrasion Resistance foam coating makes these HyFlex<sup>®</sup> gloves 12x more abrasion-resistant
- Lightened feel: HyFlex<sup>®</sup> 11-931 PPE gloves' ultralight 18-gauge design and ERGOFORM™ Technology deliver optimal dexterity
- Enhanced grip: ANSELL GRIP™ coating treatment reduces the force needed to sustain grip, preventing workplace injuries
- Elevated comfort: ZONZ™ Comfort Fit's knitting and stitch design lessens hand fatigue, for flexible, cossetting industrial gloves



#### **Industries**

- Automotive
- Automotive Aftermarket
- Machinery and Equipment
- Metal fabrication
- Agriculture
- Oil and gas
- Utilities
- Warehousing

#### **Applications**

- Inspection, selecting, checking parts
- Assembly & inspection of components
- Picking, fastening components
- Chassis assembly, body trimming
- Adjusting parts, systems
- Delivery of parts to production line
- Equipment repair & maintenance
- Engine transmission and repair
- Oil, fluids and filter change
- Inspection (picking, checking and marking)
- Feeding the press and removing spare parts from it
- Fastening components, parts
- Adjusting panels parts components
- Press shop operations





## 11-931

Lightest weight gloves with cut + oil protection for enhanced safety

#### **Key Features**

- RIPEL™ Liquid Repellence: Defense from oil and chemicals
- Reinforced thumb crotch: 12x greater durability around the thumb\*
- Ultralight 18-gauge design: All-day comfort and dexterity \*compared to competitor gloves lacking this feature

#### **Technologies**



















### **Performance Standards & Regulatory Compliance**

















**STANDARD** 100 4419CIT

#### **Specifications**

BRAND   STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex <sup>®</sup> 11-931	Finishing: Palm Coated Coating Material: Foam Nitrile Liner Material: Dyneema® Diamond Technology		6, 7, 8, 9, 10, 11	212-261 mm / 8.3-10.3 in.	Grey and Black	12 pairs / polybag, 12 polybags per case = 144 pairs / case

#### For additional information visit us at www.ansell.com, or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C, BIVA. Bernardo Quintana No. 70 Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

#### North America Region Ansell Healthcare Products LLC

111 Wood Avenue South, Suite 900 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Ansell Canada 105 Lauder Cowansville, QC J2K 2K8 T: +1 800 363 8340

#### Australia

Ansell Limited Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 T: +603 8310 6688 F: +603 8310 6699

Ansell, <sup>®</sup> and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

