Comfortable gloves offering tactility and protection across numerous applications

- **Elevated comfort:** Ansell MICROFLEX® 92-134 Versatility disposable safety gloves are made of a soft nitrile formulation, which provides a highly comfortable fit and feel while protecting hands

- **Heightened tactility:** These nitrile disposable gloves' lightweight construction provides augmented tactile sensitivity and fine motor control

- **Optimized grip:** These MICROFLEX® gloves are textured on the fingertips to ensure a stronger grip for the safer handling of tools and materials

- **Genuine versatility:** Designed for a broad range of applications, these gloves reinforce hand protection across a wide range of industries

Industries

- Healthcare
- Automotive
- Food Processing
- Janitorial / Sanitation
- Manufacturing
- Life Sciences
- Government

Recommended For

- Standard patient examinations
- Picking parts and accessories
- Food processing and handling
- Catering/Meal preparation
- Disposal of waste (trash, biohazard and linens)
- Light assembly tasks
- Lab work, blending, compounding, filling, cleaning
- Preparing pharmaceutical products
- Laboratory analysis

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, Korean Standard, ASTM D6319, CE 0493, IFU, EN 16523-1, EN ISO 374-1:2016 Type B JKT, EN ISO 374-5:2016 Virus, EN 455 1-4, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade, EU Food Contact Approved, ISO 13485, ISO 18889:2019, ISO 9001, PMDA Notification Number: 13B3X10307AH0001, Trade Name: Ansell Non Latex Medical Examination Glove, UKCA, Anvisa 81496190020 / CA 48.121, INVIMA 2015DM-0013417
Packaging Overview	100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case | 90 gloves per dispenser (Size XXL), 900 gloves per case (Size XXL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China, Malaysia
Product Segmentation	Standard Thin
Antistatic	No
Silicone Free	No
Vulcanization Chemical Accelerators	• Zinc Dibutyldithiocarbamate (ZDBC) • Zinc Diethyldithiocarbamate (ZDEC) *Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.*

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D6319
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D6319
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D6319
	BEFORE AGING	**AFTER AGING**	
Ultimate Tensile Strength (MPa)	≥ 14	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412 & D573
Force at break (N)	≥ 6	≥ 6	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	92134060	92134070	92134080	92134090	92134100	92134110

Performance Standards and Regulatory Compliance

CE 0493 | EN ISO 374-1:2016 Type B J K T | EN ISO 374-5 VIRUS | ISO 13485 | ISO 18889 G1 | ISO 9001 | MD | UKCA

Ansell