

# 69-318

Lightweight Latex Exam Glove with Enhanced Tactility

# Lightweight latex gloves that provide superior comfort and tactility

- Exceptional fit and feel: Made from highquality elastic latex, TouchNTuff<sup>®</sup> 69-318 gloves offer superior comfort
- Heightened sensitivity: The thin design provides excellent tactility when compared to standard latex gloves
- Secure handling: Textured fingers for easy handling of small objects and delicate instruments
- Food handling compliance: These gloves are food-handling compliant, and thus are suitable for a wide variety of food handling applications

CAUTION: This product contains natural rubber latex, which may cause allergic reactions



# **Industries**

- Life Sciences
- Food Processing
- Chemical

#### **Recommended For**

- Sample taking and processing
- Testing
- Vehicle maintenance
- Food contact
- All food processing, applications that have food contact
- Food processing and handling
- Meat, Fish and Food Processing
- Secondary food processing



# **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Category III, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 13485, ISO 9001, UKCA
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Multi-Purpose
Antistatic	Not Tested
Silicone Free	Yes

# **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	240 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 /	ASTM D5151,EN 455-1	
Palm Thickness (mm/mils)	0.12/	ASTM D3767,EN 420	
Finger Thickness (mm/mils)	0.14	ASTM D3767,EN 420	
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 650	≥ 500	ASTM D412

#### **ORDERING INFORMATION**

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	69318060	69318070	69318080	69318090	69318100

### **Performance Standards and Regulatory Compliance**













## For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01 Asia Pacific Region MY +603 8310 6688

apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151 info.medical.ip@ansell.com

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445 Latin America & Caribbean Region

BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and TM are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a

