

**85-304**Non-clean/Non-sterile CSM
RABS/Isolator Gloves

## Chemical-resistant cleanroom gloves, offering hard-wearing personal protection

Port size: 305mm/12"
Thickness: 0.4mm/16 mil

- Specialized defenses: Ansell's AlphaTec® CSM Isolator Glove 85-304 is highly resistant against concentrated acids and bases, ensuring advanced workplace safety and the prevention of workplace injuries
- Elevated comfort: These cleanroom gloves are made from soft, flexible material, resulting in comfortable, easyto-use CSM gloves
- Optimized glove life: The AlphaTec® CSM Isolator Glove 85-304 is designed to withstand exposure to oxygen, UV rays and ozone without rapidly aging
- Limited contamination risks: These isolator gloves' white color also makes contamination easier to detect

#### **KEY FEATURES & BENEFITS**

- Sturdy CSM composition: Protection from concentrated acids and bases
- Flexible material: For softness, comfort and everyday usability
- Durable design: Resistant against oxygen, UV ray and ozone exposure







# **85-304**Non-clean/Non-sterile CSM RABS/Isolator Gloves

#### **TECHNICAL DATA SHEET**

Product Reference	85-304
Material	Chlorosulfonated polyethylene_CSM
Color	White
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 120°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN ISO 374-5:2016, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, Category III, UKCA





### 85-304 Non-clean/Non-sterile CSM **RABS/Isolator Gloves**

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	800 / 32	EN ISO 21420
Port Size	305mm/12"	
Target Single Wall Palm Thickness (mm/mil)	0.4 / 16	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.4 / 16	EN 455-2

#### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 3	
Blade Cut Resistance	Level 1	
Tear Resistance	Level O	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

#### **ORDERING INFORMATION**

	PORT SIZE	12"/305mm	12"/305mm
	SIZE	9.5	11
85-304	REORDER NO.	85304095	85304110

**Performance Standards and Regulatory Compliance** 









#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890





