

MidKnight® MK-296

Distinctive, Black Nitrile Exam Glove

Black nitrile gloves that mask stains

- Masks stains: MICROFLEX[®]
 MidKnight[®] MK-296 exam gloves' black color disguises dirt while enhancing the visibility of light-colored objects
- Enhanced grip: A fully textured, nonfoaming design offers these powderand silicone-free nitrile gloves superior grip
- Proven protection: These medical exam gloves are approved for use against fentanyl and gastric acid (vomit), ensuring they are suitable for hazardous overdose situations
- Genuine versatility: These gloves are suitable for various applications, used notably by auto mechanics, maintenance workers and law enforcement officers
- Food handling compliant: Also ideal for a wide range of food handling applications



Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Healthcare
- Emergency Medical Services
- Utilities
- Warehousing

Recommended For

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Use of cleaning tools and robotic equipment
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Blending, compounding solids and liquids
- Raw material sample collection
- Weighing and dispensing of solid and liquid raw materials
- Inspection (picking, checking and marking)
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients



TECHNICAL DATA SHEET

	Product Information	
External Glove Surface	Fully Textured	
Audit Standards	ISO 13485:2003	
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case Also available in retail packs 10 gloves per pack 50 packs per carton/case	
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country Of Origin	Malaysia	
Product Segmentation	Robust	
Antistatic	Yes	

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	245 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.11 / 4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.15 / 6.0		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	24	20	ASTM D412 & D573
Elongation at Break (%)	600	500	ASTM D412
Force at break (N)	7	6	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	MK-296-XS	MK-296-S	MK-296-M	MK-296-L	MK-296-XL	MK-296-XXL

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell. CO: +57 1 288 3247 latam.medical@ansell.

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, $^{\textcircled{8}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{C}}$ 2024 Ansell Limited. All Rights Reserved.

